Mr./Mrs/Ms:	Model: Reg.No: _	
Invoice/Job no:	Odometer reading: V.I.N:	
Service type:	FS FS A B A B A B	MINI
Months/,000 mile	s: 1 6 12 24 36 48 60 72 84 96	
Adjust/Lubricate	Replace - Labour cost included in scheduled time except items marked *	(ALL MODELS)
Check - After the	e checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labor	ur and material cost. MAINTENANCE CHECK SHEET
	PRELIMINARY	A B MAIN SERVICE
1.	Before commencing work, check for any outstanding service actions.	36. Check handbrake operation
FS	FIRST SERVICE	37. Lubricate strikers, latches (use Rover lock grease) door hinges and door checks
2. 1k	Torque cylinder head fixings - First 1000 miles only	38. Check front screen number plates and V.I.N- 36 months and then every 12 months
3. 1k	Adjust valve clearances - First 1000 miles only	39. Check seatbelt and airbag module covers - 36 months and then every 12 months
3. <u>1k</u>	Check and adjust steering track- First 1000 miles only (with sports pack fitted)	40. Check tyre pressures, condition and tread depth(mm)
4 5. 6k	Replace engine oil and filter- All models, First 6000 miles only	LHF RHF RHR LHR Spare
A B	MAIN SERVICE	41 Check lamps, horns, and system warning indicators
	_	42 Check screen wipers and washers
6.	Annual corrosion/cosmetic inspection - Using annual corrosion inspection sheet	42. Replace alarm handset batteries
7.	Replace engine oil and filter	10 YEAR REPLACEMENT - AIRBAGS
8.	Replace oil filler breather cap	
9.	Replace antifreeze - 36k and then every 24k	Carry out the replacement of the airbag modules and rotary coupler regardless of mileage after 10 years.
10.	Check battery connections and antifreeze	
11.	Check brake & clutch fluid levels	44. Replace airbag module(s)
12.	Check pressure sensing hoses and vacuum pipes	AFTER EACH MAIN SERVICE
13.	Adjust clutch/return stop	45. Check oxygen sensor operation - at 36 months and then every 12 months
14.	Adjust valve clearances	46. Check CO at tailpipe- at 36 months and then every 12 months. (Record CO%)
15.	Check cooling system hoses and connections for signs of leakage and condition	47. Carry out engine tuning - (Carb models only). (Record CO%)
16.	Check fuel & clutch pipes and hoses for signs of leakage and condition	48. Carry out road test, check for the correct function of all vehicle systems
17.	Check condition of crankcase vent hoses & valves where fitted	The maintenance items listed, are those recommended for vehicles operating under normal driving, road and climatic conditions. More
18.	Check air conditioning system, hoses and sight glass	frequent attention may be necessary if the vehicle is subject to stop/start operation, extremes of temperature, dusty conditions or frequent
19.	Check water pump and auxiliary drive belts tension and condition	towing of trailers.
20.	Lubricate carburettor piston damper	Service check completed, cosmetic/corrosion inspection check completed and service portfolio book stamped
21.	Replace air cleaner element	
22. 48k		Name: Date:
23.	Replace contact breaker points	
24.	Replace spark plugs - Non catalyst Models	
25.	Replace spark plugs - With catalyst fitted	
26.	Replace brake fluid - Every 24 months regardless of mileage*(indicate replacement on service record)	
27.	Check exhaust system and heat shields	
28.	Remove rear road wheels	
29.	Check rear brake linings, drums, cylinders, hoses and pipes	
30.	Remove front road wheels	
31.	Check road wheels, front brake linings, cylinders, disc, calipers, drums, cylinders, hoses and pipes	
32.	Check suspension and steering for signs of leaking or wear	
33.	Check wheel bearings, drive shafts and gaiters	
34.	Lubricate suspension pivots, ball joints, handbrake clevis pins and quadrants	
35.	Adjust handbrake - First 12,000 miles only	

Mr./Mrs/Ms:	Model: Reg.No: _	
Invoice/Job no:	Odometer reading: V.I.N:	
Service type:	FS FS A B A B A B	MINI
Months/,000 mile	s: 1 6 12 24 36 48 60 72 84 96	
Adjust/Lubricate	Replace - Labour cost included in scheduled time except items marked *	(ALL MODELS)
Check - After the	e checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labor	ur and material cost. MAINTENANCE CHECK SHEET
	PRELIMINARY	A B MAIN SERVICE
1.	Before commencing work, check for any outstanding service actions.	36. Check handbrake operation
FS	FIRST SERVICE	37. Lubricate strikers, latches (use Rover lock grease) door hinges and door checks
2. 1k	Torque cylinder head fixings - First 1000 miles only	38. Check front screen number plates and V.I.N- 36 months and then every 12 months
3. 1k	Adjust valve clearances - First 1000 miles only	39. Check seatbelt and airbag module covers - 36 months and then every 12 months
3. <u>1k</u>	Check and adjust steering track- First 1000 miles only (with sports pack fitted)	40. Check tyre pressures, condition and tread depth(mm)
4 5. 6k	Replace engine oil and filter- All models, First 6000 miles only	LHF RHF RHR LHR Spare
A B	MAIN SERVICE	41 Check lamps, horns, and system warning indicators
	_	42 Check screen wipers and washers
6.	Annual corrosion/cosmetic inspection - Using annual corrosion inspection sheet	42. Replace alarm handset batteries
7.	Replace engine oil and filter	10 YEAR REPLACEMENT - AIRBAGS
8.	Replace oil filler breather cap	
9.	Replace antifreeze - 36k and then every 24k	Carry out the replacement of the airbag modules and rotary coupler regardless of mileage after 10 years.
10.	Check battery connections and antifreeze	
11.	Check brake & clutch fluid levels	44. Replace airbag module(s)
12.	Check pressure sensing hoses and vacuum pipes	AFTER EACH MAIN SERVICE
13.	Adjust clutch/return stop	45. Check oxygen sensor operation - at 36 months and then every 12 months
14.	Adjust valve clearances	46. Check CO at tailpipe- at 36 months and then every 12 months. (Record CO%)
15.	Check cooling system hoses and connections for signs of leakage and condition	47. Carry out engine tuning - (Carb models only). (Record CO%)
16.	Check fuel & clutch pipes and hoses for signs of leakage and condition	48. Carry out road test, check for the correct function of all vehicle systems
17.	Check condition of crankcase vent hoses & valves where fitted	The maintenance items listed, are those recommended for vehicles operating under normal driving, road and climatic conditions. More
18.	Check air conditioning system, hoses and sight glass	frequent attention may be necessary if the vehicle is subject to stop/start operation, extremes of temperature, dusty conditions or frequent
19.	Check water pump and auxiliary drive belts tension and condition	towing of trailers.
20.	Lubricate carburettor piston damper	Service check completed, cosmetic/corrosion inspection check completed and service portfolio book stamped
21.	Replace air cleaner element	
22. 48k		Name: Date:
23.	Replace contact breaker points	
24.	Replace spark plugs - Non catalyst Models	
25.	Replace spark plugs - With catalyst fitted	
26.	Replace brake fluid - Every 24 months regardless of mileage*(indicate replacement on service record)	
27.	Check exhaust system and heat shields	
28.	Remove rear road wheels	
29.	Check rear brake linings, drums, cylinders, hoses and pipes	
30.	Remove front road wheels	
31.	Check road wheels, front brake linings, cylinders, disc, calipers, drums, cylinders, hoses and pipes	
32.	Check suspension and steering for signs of leaking or wear	
33.	Check wheel bearings, drive shafts and gaiters	
34.	Lubricate suspension pivots, ball joints, handbrake clevis pins and quadrants	
35.	Adjust handbrake - First 12,000 miles only	

GLOSSARY

FIRST SERVICE= The first service required after sale of vehicle. This service is only applicable to certain models as indicated by the maintenance check sheet.

LUBRICATION SERVICE = The lubrication service is carried out between main services, the first at 18 months or 18,000 miles, whichever occurs first, and then at every subsequent 12 months or 12,000 miles. It is only applicable to certain derivatives as indicated by the maintenance check sheet.

MAIN SERVICE = The main service is applicable to all vehicles. It is carried out at 12 month or 12,000 miles intervals, whichever occurs first.

Main Service "A" is applicable at 12 months/12,000 miles, 36 months/36,000 miles, 60 months/60,000 miles 84 months/84,000 miles and so on.

Main Service "B" is applicable at 24 months/24,000 miles, 48 months/48,000 miles, 72 months/72,000 miles, 96 months/96,000 miles and so on. Some items do not need to be carried out at every main service and these items are identified by an indicator in the tick box e.g. 60k (This indicates that this item is only applicable every 60 months/ 60,000 miles)

For full details regarding the operations contained in this maintenance check sheet, please refer to the workshop manual.